



Specifications:
 Contact Resistance: 30mΩ max.at DC 100 mA
 Insulator Resistance: 1000MΩ min.at DC 500V
 Current Rating: 1AMP

Dielectric Withstanding
 Voltage: AC 1000V For 1 minute
 Operating Temperature:-55°C--+105°C
 Contact: Phosphor bronze
 Housing: PBT 830% Glass Fiber(UL 94V-0)

Position	A	B
8	14.73	7.62
10	17.27	10.16
14	22.35	15.24
16	24.89	17.78
20	29.97	22.86
25	37.59	28.48
30	42.67	35.56
34	47.75	40.64
40	55.37	48.26
50	68.07	60.95
60	80.77	73.65
64	85.85	78.74

序号/revno. 更改记录/revision record 签名/signature 日期/date

设计/Designed by: 绘图/Drawing by: 审核/checked by: 批准/Approved by: 本图公差 General Tolerance

新莱亚电子
 XINLAIYA ELECTRONIC CO., LTD
 图名/Title: 110
 文件编号/Title No.:
 页序/Sheet:
 备注/Remark:
 单位/unit(s):

公差:
 X. ±0.2 X. ±2°
 .X ±0.1 .X° ±1°
 .XX ±0.05 .XX° ±0.5°
 .XXX ±0.01