



Specifications:
Contact Resistance: 30mΩ max.at DC 100 mA
Insulator Resistance: 1000MΩ min.at DC 500V
Current Rating: 1AMP

Dielectric Withstanding
Voltage: AC 500V For 1 minute
Operating Temperature:-55°C--+105°C
Contact: Phosphor bronze
Housing: PBT 830% Glass Fiber(UL 94V-0)

Position	Dimension			
	A	B	C	D
6	7.52	7.62	10.16	7.62
8	10.16	7.62	10.16	7.62
14	17.82	15.24	10.16	7.62
16	20.32	17.78	10.16	7.62
18	22.86	20.32	10.16	7.62
20	25.40	22.86	10.16	7.62
24	30.48	27.94	10.16	7.62
24	30.48	27.94	17.78	15.24
28	35.56	33.02	10.16	7.62
28	35.56	33.02	17.78	15.24
40	50.80	48.26	17.78	15.24

- 要求:**
1. 塑料件无裂痕。
 2. 整排端子成一直线，相邻端子之间相互平行。

设计/Designed by	绘图/Drawing by	审核/Checked by	批准/Approved by	本图公差 General Tolerance
				X: ±0.2 X: ±2° .X: ±0.1 .X: ±1° .XX: ±0.05 .XX: ±0.5° .XXX: ±0.01
新莱亚电子 XINLEIYA ELECTRONIC CO., LTD		图名/Title	文件编号/File No.	
		128	页序/Sheet	
备注/Remark				单位/Unit(s): 数量